

Electric Stackers-TL Series

Our full electric stacker is assembled from high quality components, and realizes stepless speed regulation. It is able to lift 1T load 5.5 meters off the ground, and lift 2T load 3 meters. The battery cell can be installed from three directions. The stacker employs an auto-induction pedal, which can automatically lower the speed when the pedal is stowed, thus adapting to the walking speed of the operator.

Model No.		TL1025	TL1030	TL1035	TL1525	TL1530	TL1535	TL2025
Rated Capacity	kg	1000			1500			2000
Load Center		500			400			
Max. Fork Height		2500	3000	3500	2500	3000	3500	2500
Max. Machine Height		2975	3475	3975	2975	3475	3975	3095
Handle Height		1385-1405			1385-1405			
Fork Size	mm	1125*160			1125*160			1125*180
Fork Width		570			570			590
Min. Turning Radius		1700			1750			
Wheel Base		1348			1398			
Front-Wheel Distance		370			320			
Max. Speed Without Load	km/h	4.5-5			5-6			
Max. Speed With Load		3.8-4.2			4-5			
Max. Travel Grade	%	8-10			8-10			
Driving Motor	v/kw	24/1.2			24/1.2-1.3			
Lifting Motor		24/2-3			24/2-3			
Battery	v/Ah	24/240-270			24/240-270			
Charger	v/A	24/30-40			24/30-40			
Overall Length	mm	2040			2040			
Overall Width		856			856			
Overall Height		1770	2020	2270	1770	2020	2270	1890
Overall Net Weight	kg	858	880	900	888	910	930	988

